Certificate of Compliance

Certificate Number:

[E543147]

Report Reference:

E543147-20240814

Issue Date:

2024-AUGUST-14

Issued to:

LEDYI LIGHTING (HK) CO.,LTD

Unit 1507c, 15/F, Eastcore 398 Kwun Tong Road

KWUN TONG KI HK

This certificate confirms that representative samples of:
LUMINAIRES AND FORMING SHELLS
See addendum page for models

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:
[UL 676 - Underwater Luminaires and Submersible Junction Boxes
CSA C22.2 NO. 89 - Swimming-Pool Luminaires, Submersible Luminaires and Accessories]

Additional Information:
See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2023 UL LLC. All rights reserved.

Certificate of Compliance

Certificate Number: E543147
Report Reference: E543147-20240814
Issue Date: 2024-AUGUST-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LY-X2428161768Y (!)
LY-X2450161768Y (!)
(!) refers to where “X” may be A, E, W, S, F, C, N, D, SK, R, G, B, P, T, RGB, RGBW, RGBD, RGBT for LED color, “A” means 2100K, “E” means 2400K,“W” means 2700K, “S” means 3000K, “F” means 3500K, “C” means 4000K, “N” means 5000K, “D” means 6500K, “SK” means 10000K, “R” means Red, “G” means Green, “B” means Blue, “P” means Pink, “T” means Color Turnable, “RGB” means integrate of Red, Green and Blue, “RGBW” means integrate of Red, Green, Blue and Warm Write, “RGBD” means integrate of Red, Green, Blue and Daylight, “RGBT” means integrate of Red, Green, Blue and Color Turnable, “Y” may be T or S for bending direction. ”T” means Top Bending, “S” means Side Bending.

LY-X2450161768Y-D (@)
where “X” may be A, E, W, S, F, C, N, D, SK, R, G, B, P, T, RGB, RGBW, RGBD, RGBT for LED color, “A” means 2100K, “E” means 2400K,“W” means 2700K, “S” means 3000K, “F” means 3500K, “C” means 4000K, “N” means 5000K, “D” means 6500K, “SK” means 10000K, “R” means Red, “G” means Green, “B” means Blue, “P” means Pink, “T” means Color Turnable, “RGB” means integrate of Red, Green and Blue, “RGBW” means integrate of Red, Green, Blue and Warm Write, “RGBD” means integrate of Red, Green, Blue and Daylight, “RGBT” means integrate of Red, Green, Blue and Color Turnable, “Y” may be T or S for bending direction. ”T” means Top Bending, “S” means Side Bending. Note: The model LY-X2450161768Y-D provided with DMX512/SPI control mode.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2023 UL LLC. All rights reserved.